

JC13 Rec'd PCT/PTO 12 MAR 2002

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Takayuki Toyoshima et al.
Serial No. : Unassigned
Filed : Herewith
Title : OPTICAL ELEMENT HAVING WAVELENGTH SELECTIVITY

BOX PCT

Commissioner for Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Prior to examination, please amend the application as follows:

In the specification:

Replace the heading beginning at page 1, line 1, with the following rewritten heading:

--Title of Invention--

Replace the heading beginning at page 1, line 4, with the following rewritten heading:

--Background of the Invention--

Delete the heading beginning at page 1, line 11.

Replace the heading beginning at page 4, line 8, with the following rewritten heading:

--Brief Summary of the Invention--

Replace the heading beginning at page 6, line 25, with the following rewritten heading:

--Brief Description of the Drawings--

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL116535227US

I hereby certify under 37 CFR §1.10 that this correspondence is being deposited with the United States Postal Service as Express Mail Post Office to Addressee with sufficient postage on the date indicated below and is addressed to the Commissioner for Patents, Washington, D.C. 20231.

Date of Deposit 3-12-02

Signature Henry Jenkins

Typed or Printed Name of Person Signing Certificate
Henry Jenkins

Applicant : Takayuki Toyoshima et al.
Serial No. : Unassigned
Filed : Herewith
Page : 2

Attorney's Docket No.: 13630-
004US1 / P3P2001052US

Replace the heading beginning at page 8, line 12, with the following rewritten heading:

--Detailed Description of the Invention--

Replace the heading beginning at page 8, line 13, with the following rewritten heading:

--First Embodiment--

Replace the heading beginning at page 13, line 4, with the following rewritten heading:

--Second Embodiment--

Replace the heading beginning at page 15, line 9, with the following rewritten heading:

--Third Embodiment--

Replace the heading beginning at page 16, line 11, with the following rewritten heading:

--Fourth Embodiment--

In the claims:

Amend claims 1-13 as follows:

--1. (Amended) An optical element having wavelength selectivity comprising:
a lens array having a first end face and a plurality of lenses arranged on the first
end face; and

a multi-layered film filter which is formed on the first end face of the lens array
and includes high refractive-index dielectric layers and low refractive-index dielectric layers
laminated alternately and whose film thickness continuously changes in accordance with
positions of the individual lenses.--

--2. (Amended) The optical element according to Claim 1, wherein the plurality of
lenses are aligned in a line from a first end of the first end face of the lens array toward a second
end of the first end face and the film thickness of the multi-layered film filter linearly changes
from the first end toward the second end.--

Applicant : Takayuki Toyoshima et al.
Serial No. : Unassigned
Filed : Herewith
Page : 3

Attorney's Docket No.: 13630-
004US1 / P3P2001052US

--3. (Amended) The optical element according to Claim 1, wherein the lens array is a rod lens array including a plurality of rod lenses.--

--4. (Amended) The optical element according to Claim 1, wherein the lens array is a gradient index planar microlens including a single substrate and a plurality of microlenses formed in a line on the substrate.--

--5. (Amended) The optical element according to Claim 4, wherein the plurality of microlenses protrude from the substrate.--

--6. (Amended) The optical element according to Claim 1, wherein the lens array has a second end face facing the first end face; and
the optical element further has a light emitting device formed on the second end face for emitting light toward the multi-layered film filter via individual lenses of the lens array.--

--7. (Amended) The optical element according to Claim 6, wherein the light emitting device is integral with the lens array.--

--8. (Amended) The optical element according to Claim 6, wherein the light emitting device includes a plurality of light sources provided in association with individual lenses of the lens array.--

--9. (Amended) The optical element according to Claim 1, wherein the lens array has a second end face facing the first end face; and
the optical element further has a plurality of light receiving elements formed on the second end face for respectively receiving a plurality of optical signals having different center wavelengths, obtained by demultiplexing input light by the multi-layered film filter, via individual lenses of the lens array.--

Applicant : Takayuki Toyoshima et al.
Serial No. : Unassigned
Filed : Herewith
Page : 4

Attorney's Docket No.: 13630-
004US1 / P3P2001052US

--10. (Amended) The optical element according to Claim 9, wherein the plurality of light receiving elements are integral with the lens array.--

--11. (Amended) A method of manufacturing an optical element having wavelength selectivity, comprising:

a step of preparing a lens array having a first end face and a plurality of lenses arranged on the first end face; and

a step of directly forming a multi-layered film filter on the first end face of the lens array by a physical vapor deposition method in such a way that the film thickness continuously changes in accordance with positions of the plurality of individual lenses.--

--12. (Amended) The optical element manufacturing method according to Claim 11, further comprising:

a step of arranging the lens array in such a way that the first end face of the lens array is inclined with respect to an evaporation source or a target, prior to the step of forming the multi-layered film filter.--

--13. (Amended) The optical element manufacturing method according to Claim 12, further comprising:

a step of arranging a film thickness correcting plate having a substantially trapezoidal opening portion between the lens array and the evaporation source or target, prior to the step of forming the multi-layered film filter.--

Applicant : Takayuki Toyoshima et al.
 Serial No. : Unassigned
 Filed : Herewith
 Page : 5

Attorney's Docket No.: 13630-
 004US1 / P3P2001052US

REMARKS

Applicant respectfully requests entry of the amendments to the specification and claims as shown herein. The specification has been amended to include US-style headings. The claims have been amended to eliminate multiple dependency and introduce US-style verbiage in the claims. No new matter has been added.

Please apply any other charges or credits to Deposit Account No. 06-1050, referencing attorney docket no. 13630-004US1.

Respectfully submitted,

Date: 3-12-02

Y. Rocky Tsao
 Y. Rocky Tsao
 Reg. No. 34,053

Fish & Richardson P.C.
 225 Franklin Street
 Boston, Massachusetts 02110-2804
 Telephone: (617) 542-5070
 Facsimile: (617) 542-8906

Applicant : Takayuki Toyoshima et al.
Serial No. : Unassigned
Filed : Herewith
Page : 6

Attorney's Docket No.: 13630-
004US1 / P3P2001052US

Version with markings to show changes made

In the specification:

Heading beginning at page 1, line 1, has been amended as follows:

[DESCRIPTION] Title of Invention

Heading beginning at page 1, line 4, has been amended as follows:

[[Technical Field]] Background of the Invention

Heading beginning at page 1, line 11, has been amended as follows:

[[Background Art]]

Heading beginning at page 4, line 8, has been amended as follows:

[[Disclosure of Invention]] Brief Summary of the Invention

Heading beginning at page 6, line 25, has been amended as follows:

[[Brief Description of the Drawings]]

Heading beginning at page 8, line 12, has been amended as follows:

[[Best Mode for Carrying Out the Invention]] Detailed Description of the Invention

Heading beginning at page 8, line 13, has been amended as follows:

[[First Embodiment]]

Heading beginning at page 13, line 4, has been amended as follows:

[[Second Embodiment]]

Applicant : Takayuki Toyoshima et al.
 Serial No. : Unassigned
 Filed : Herewith
 Page : 7

Attorney's Docket No.: 13630-
 004US1 / P3P2001052US

Heading beginning at page 15, line 9, has been amended as follows:

[[Third Embodiment]]

Heading beginning at page 16, line 11, has been amended as follows:

[[Fourth Embodiment]]

In the claims:

Claims 1-13 have been amended as follows:

1. (Amended) An optical element having wavelength selectivity[, characterized by] comprising:

a lens array having [one] a first end face and a plurality of lenses [(L1-L8)] arranged on the [one] first end face; and

a multi-layered film filter [(13)] which is formed on the [one] first end face [(14)] of the lens array and includes high refractive-index dielectric layers and low refractive-index dielectric layers laminated alternately and whose film thickness continuously changes in accordance with positions of the individual lenses.

2. (Amended) The optical element according to Claim 1, [characterized in that] wherein the plurality of lenses are aligned in a line from a first end of the first end face of the lens array toward a second end [from a first end of the one] of the first end face [of the lens array] and the film thickness of the multi-layered film filter linearly changes from the first end toward the second end [from the first end].

3. (Amended) The optical element according to Claim 1 [or 2], [characterized in that] wherein the lens array is a rod lens array including a plurality of rod lenses.

4. (Amended) The optical element according to Claim 1 [or 2], [characterized in that] wherein the lens array is a gradient index planar microlens [(50, 60)] including a single substrate [(59, 69)] and a plurality of microlenses [(51-56, 61-66)] formed in a line on the

Applicant : Takayuki Toyoshima et al.
 Serial No. : Unassigned
 Filed : Herewith
 Page : 8

Attorney's Docket No.: 13630-
 004US1 / P3P2001052US

substrate.

5. (Amended) The optical element according to Claim 4, [characterized in that] wherein the plurality of microlenses [(61-66)] protrude from the substrate.

6. (Amended) The optical element according to [any one of Claims 1 to 5] Claim 1, [characterized in that] wherein the lens array has [an other] a second end face [(24)] facing the [one] first end face; and

the optical element further has a light emitting device [(30)] formed on the [other] second end face for emitting light toward the multi-layered film filter via individual lenses of the lens array.

7. (Amended) The optical element according to Claim 6, [characterized in that] wherein the light emitting device is integral with the lens array.

8. (Amended) The optical element according to Claim 6 [or 7], [characterized in that] wherein the light emitting device includes a plurality of light sources [(LD1-LD8)] provided in association with individual lenses of the lens array.

9. (Amended) The optical element according to [any one of Claims 1 to 5] Claim 1, [characterized in that] wherein the lens array has [an other] a second end face facing the [one] first end face; and

the optical element further has a plurality of light receiving elements [(PD1-PD8)] formed on the [other] second end face for respectively receiving a plurality of optical signals having different center wavelengths, obtained by demultiplexing input light by the multi-layered film filter, via individual lenses of the lens array.

10. (Amended) The optical element according to Claim 9, [characterized in that] wherein the plurality of light receiving elements are integral with the lens array.

Applicant : Takayuki Toyoshima et al.
Serial No. : Unassigned
Filed : Herewith
Page : 9

Attorney's Docket No.: 13630-
004US1 / P3P2001052US

11. (Amended) A method of manufacturing an optical element having wavelength selectivity, [characterized by] comprising:

a step of preparing a lens array [(12)] having [one] a first end face and a plurality of lenses [(L1-L8)] arranged on the [one] first end face; and

a step of directly forming a multi-layered film filter on the [one] first end face of the lens array by a physical vapor deposition method in such a way that the film thickness continuously changes in accordance with positions of the plurality of individual lenses.

12. (Amended) The optical element manufacturing method according to Claim 11, further [characterized by] comprising:

a step of arranging the lens array in such a way that the [one] first end face of the lens array is inclined with respect to an evaporation source or a target, prior to the step of forming the multi-layered film filter.

13. (Amended) The optical element manufacturing method according to Claim 12, further [characterized by] comprising:

a step of arranging a film thickness correcting plate [(70)] having a substantially trapezoidal opening portion [(71)] between the lens array and the evaporation source or target, prior to the step of forming the multi-layered film filter.